Docket No.: YOR919990588US2

IN THE SPECIFICATION:

5

10

15

20

25

30

Please amend the paragraph beginning at page 4, line 16, as follows.

Another problem with the prior art is that only one static fingerprint or palm-print image is grabbed during acquisition of the biometrics biometres signal. This instant image may be a distorted depiction of the ridges and valley structure on the finger or palm because the user exerts force, torque and/or pressure with the finger with respect to the image acquisition device (fingerprint or palm-print reader). A problem is that, without grabbing more than one image or modifying the mechanics of the sensor, it cannot be detected whether the image is acquired without distortion. An additional problem with the prior art of grabbing a static fingerprint image and representing a static fingerprint image is that there is only one choice for the image that can be used for person authentication and that image may not be the best depiction of the ridge-valley structure.

Please amend the paragraph beginning at page 12, line 11, as follows.

Figure 4 is a generic block diagram for combining a biometrics with user action, i.e., combining biometrics at the subject level. The user action, just like the movement of a pen to produce a signature, is the second behavioral biometrics. The user 410 offers a traditional biometric 420 for authentication or identification purposes. Such a biometrics could be a fingerprint, iris or face. However, rather than holding the biometrics still, as in the case of fingerprints or faces, or keeping the eyes open, as in case of iris recognition, the user performs some specific action 430, a(t) with the biometrics. This action is performed over time 432, from time 0 (434) to some time T (436). Hence, the action a(t) is some one-dimensional function of time 430 and acts upon the traditional biometric 420. Note that this biometric is the actual biometric of user 410 and not a biometrics signal (i.e., in the case of fingerprints, it is the three-dimensional finger with the print on it). It is specified what the constraints of the action 430 are but within these constraints, the user 410 can define the action. (For example, constraints for putting a signature are that the user can move the pen over the paper in the x- and y-direction but cannot move the pen in the z-direction.) That is, the action 430 in some sense transforms the biometric of the user over time. It is this transformed biometric 450 that is input to the biometric signal recording device 460. The output 470 of this device is a sequence of individually transformed biometrics signals B(t) 480 from time 0 (434) to some time T (436). In the case of fingerprints, these are fingerprint images, in the case of face, these are face images. This output sequence 470, is the input 485 to some extraction algorithm 490. The extraction algorithm computes from the sequence of transformed biometrics the pair (a'(t), B), 495, which is itself a biometric. The function a'(t) is some behavioral way of transforming biometric B over a time interval [0, T] and is related to the function a(t) which wich is chosen by the user (very much like a user would select a signature). The biometrics B can be computed from the pair (a'(t), B), that is, where a(t) 430 is zero, where there is no action of the user, the output 470 is undistorted copy of biometrics 420. In general, it can be computed where in the signal 480, the biometrics 420 is not distorted.